

Product specification



Sagsnr:	
Sag:	Belgravia S15 T 12,5 mm
Emne:	Designpanel Micro 900x2700 mm
Sign:	
Dato	2013-06-03

Perforated boards

17,35	% of Module
18,31	% of Tile
A2-s1,d0	Material Class
66,91	Light reflection
1/A/0 load	Deflection class
No	Covering class
No	Impact resistance

Regula Boards

A2-s1,d0	Material Class
81	Light reflection
1/A/0 load	Deflection class
No	Covering class
No	Impact resistance

Acoustical performance

100	Suspension distance
------------	----------------------------

		Perforated boards						Unfilled cavity	
		Perforeret 18,3122 %							
Hz		125	250	500	1000	2000	4000		
		0,25	0,40	0,56	0,64	0,65	0,63	NRC	0,55
alpha P		0,25	0,4	0,55	0,65	0,65	0,65	alpha w	0,6

		Perforated boards						50 mm mineral wool	
		Perforeret 18,3122 %							
Hz		125	250	500	1000	2000	4000		
		0,52	0,72	0,78	0,75	0,72	0,77	NRC	0,75
alpha P		0,5	0,7	0,8	0,75	0,7	0,75	alpha w	0,75

		Regula boards						Min 50 mm cavity	
Hz		125	250	500	1000	2000	4000	NRC	0,05
alpha P		0,40	0,20	0,10	0,05	0,05	0,00	alpha w	0,05

Knauf Danoline A/S
Kløvermarksvej 6
DK-9500 Hobro